

## Fiber Optic Cable


# ADSS-XOTKtsdD 2,5kN (max 5kN) 4-48 Fibres

Spec. No. 2788/1/0

13.06.2013, page 1/2



Type: aerial, non-metallic, unfilled, reinforced




Cross section of 2x6 FO cable



### Cable construction:

1. Optical fibres
2. Loose tube
3. Central element non-metallic
4. Filler
5. Waterblocking tape
6. Reinforcement – aramid yarn
7. Outer sheath
8. Ripcord

CONSTRUCTION				
Element	Type	Material	Dimension	
Fibres	ITU-T G.652D or according to the attached specifications			
Identification of fibers	Comply to IEC 60304: Red, Green, Blue, White, Violet, Orange, Grey, Yellow, Brown, Pink, Black, Turquoise			
Identification of tubes/ elements	Blue, Yellow, Natural, Green,     filler - black			
Central support member	Straight rod,	Fibre Reinforced Plastic	φ 2,3 mm	
Secondary coating	loose tube - thermoplastic material, containing 2, 4,6 or 12 fibres,	PBT	φ 2,1 mm (approx.)	
Filling of the tube	gel	Thixotropic gel		
Interstitial waterblocking	Dry sealed	Swelling tape	thickness: 0,20mm (approx.)	
Reinforcement	Dielectric yarn	Aramid		
Outer sheath	Black	extruded HDPE polymer density ≥ 0,945 g/cm <sup>3</sup>	thickness: minimum spot average	1,3mm 1,5mm
Attenuation @1310nm	≤ 0,4 dB/km *)			
Attenuation @1550nm	≤ 0,25 dB/km *)			
Marking/Printing:	FIBRE OPTIC CABLE ADSS-XOTKtsdD 24J 5kN TF Kable 1 2012  (or according to the agreement). Length marking every metre			
Standard delivery lengths	4200 ± 100 m; to be agreed			

\*) Max attenuation for SMF in cable - other parameters of the fiber according to the attached specifications

## Fiber Optic Cable

# ADSS-XOTKtsdD 2,5kN (max 5kN) 4-48 Fibres

Spec. No. 2788/1/0

13.06.2013, page 2/2



### PARAMETERS

No. of fibres in a cable	Outer diameter of tube	No. of elements in a cable (tubes/fibers)	Cable dimensions		Mechanical properties				
			Outer diameter	Cable weight	Rated working tension	Max. working tension	Rated tensile strength	Young module	Thermal expansion coefficient
	[mm]		[mm]	[kg/km]	[kN]	[kN]	[kN]	[GPa]	[1/°C]
4 - 48	2,1	6	10,5 ± 0,2	85	2,5	5,0	11,0	8,5	10,5 x 10 <sup>-6</sup>

### FEATURES

- fully dielectric and resistant to electromagnetic interferences
- secured from longitudinal water penetration
- resistant to abrasion, UV and stress corrosion

### APPLICATIONS

Cable is designated for a long distance transmission of digital and analogue signals within the whole optical bandwidth used in wide and local telecom networks of any spatial configuration. Suitable for aerial installations

All the information contained in this document - including tables and diagrams - is given in good faith and believed to be correct at the time of publication. The information does not constitute a warranty nor representation for which TELE-FONIKA Kable assumes legal responsibility. TELE-FONIKA Kable reserves rights to introduce changes to the document at any time.